







HTS SOLID COLOR FABRICS : 54.07.52.00.00.

HTS PRINTED FABRICS :

TECHNICAL INFORMATION		
BASE : 22602		FABRIC : Woven Fabric
WIDTH:	59.05 ± 0.79 in	ASTM D3774
CUTTABLE WIDTH :	58.27 ± 0.79 in	ASTM D3774
MASS PER UNIT AREA (WEIGHT) :	13.28 ± 0.47 oz/yd2	ASTM D3776 OPC. C
MARTINDALE ABRASION - BREAKDOWN:	Min 50000.00 cy	ISO 12947-2
COURSES OR PICKS:	Max 45.72 yarn/in	ASTM D3775 / ASTM D8007
FLAME RESISTANCE (CLASS):	CUM	NFPA 260
CERTIFICATE OF ORIGIN FAIL:	e	NO COUNTRY
COMPOSITION :	100.00 % PES	

22602 - Runa1809 - Runa3 - Deco

TECHNOLOGIES			USES	
NAME	DESCRIPTION	NORM		
	Decogard Durability, technology that guarantees superior durability to the market, providing excellent performance in fundamental tests on textiles for use in commercial and residential spaces.	AATCC 16	CONTRACT HEALTHCARE UPHOLSTERY	
		OPC. 3	CONTRACT HOSPITALITY UPHOLSTERY	
		AATCC 61	CONTRACT WORKPLACE UPHOLSTERY	
		AATCC 8/	HOME UPHOLSTERY , INTERIORS	
		AATCC 116		
		ASTM D2261		
		ASTM D3939		
		ASTM D5034		
		ASTM D6797		
	The FR textile protector effectively protects against fire, retarding its action and preventing its spread.	NFPA 260		

BENEFITS


- Canvas with a rustic appearance, composed of two colors of yarn, comfortable and timeless, which provides warmth to the spaces.
- Fleece backing for increased fabric stability and body.

Lafayette
Deco

- The information herein is valid from the issue date of this technical sheet 02/09/2020. Data Sheet with validity of 90 days.
 - Textiles Lafayette S.A.S reserves the right to make modifications without previous notification within its continuous improvement framework.
 - If this product is used for other uses than those mentioned in the sheet, it is at your own responsibility.
www.lafayette.com Phone Number: + 57 2948880 Calle 15 # 72 - 95 Bogotá D.C

- High quality fabric specially developed for upholstery.
- Resistant to tension and tearing.

CARE INSTRUCTIONS

- Use any commercial detergents or soaps.
- Do not store wet.
- Used a hand and soft brush to cleaning or restoring appearance.
- Vacuum every 3 months.
-  - Do not twist or wring.
- Avoid contact with rough surfaces, to prevent snagging.
- Avoid exposure to sunlight direct or through a window. It is recommended to use veil-curtains and to keep them closed.
- The stains should to clean at the less possible time using a clean duster, that's easy to remove with soft detergent, shampoos or foams for cleaning in home. All this one have to be diluted in water.

CUT AND DRESSMAKING RECOMMENDATIONS

Note: the data herein represents recommended values that may vary depending on the conditions and machines used in the different processes (dressmaking, sublimation, embroidery and fusion). We recommended conducting tests before production and identifying each process' variables and conditions to guarantee the textile's productivity and characteristics.

Cut	Unroll the fabric and let stand for 4 hours minimum, tend 5 layers maximum, no generating tension, use paper between layers draw at 0,4 inch minimum of the edge, Use blades in optimum conditions, when you cutting keep a constant and moderate speed, give adequate handling to the cut pieces.
Dressmaking	<p>Fit: tensions in machines and pressure of the foot to achieve a correct drag of the textile. Use:suitable adjustment according to the type of textile, presser foot suitable for each operation, thread and needle recommended in optimal conditions.Minimum margin of seam 0.6 inch. Do not reprocess.</p> <p>Needle Size / Thickness : 90/14</p> <p>Needle Point : R or RS.</p> <p>Size Thread : tex 45 Nylon.</p> <p>Stitch per inch : 8</p> <p>Machine Type : single needle.</p>